CASE PTFIX L-BOXX REV2 DE - System package

1164787

https://www.phoenixcontact.com/ro/produse/1164787

Vă rugăm să țineți cont de faptul că datele afișate în acest document PDF au fost generate din catalogul nostru online. Datele complete sunt disponibile în documentația pentru utilizator. În cazul descărcărilor, se aplică Termenii și condițiile generale de utilizare ale companiei noastre.



PTFIX set in a practical Sortimo L-BOXX 102 system case. 72 distribution blocks, including with feed-in contact (rated cross-section 10 mm^2) and pick-off contacts (rated cross-section 4 mm^2), 20 monoblocks (rated cross-section 2.5 mm^2), 53 DIN rail adapters, 16 screw flanges, jumpers, and marking material

Setul este alcătuit din

PTFIX 10/12X4 GY - Distribution block

3273878

https://www.phoenixcontact.com/ro/produse/3273878



Distribution block, Basic terminal block with supply, nom. voltage: 450 V, nominal current: 32 A, number of connections: 13, connection method: Push-in connection, Load contact, cross section: 0.2 mm^2 - 6 mm^2, Push-in connection, Line contact, Rated cross section: 10 mm^2, cross section: 0.5 mm^2 - 10 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: gray

PTFIX 10/12X4 BU - Distribution block

3273880

https://www.phoenixcontact.com/ro/produse/3273880




Distribution block, nom. voltage: 450 V, nominal current: 32 A, number of connections: 13, connection method: Push-in connection, Load contact, cross section: 0.2 mm^2 - 6 mm^2, Push-in connection, Line contact, Rated cross section: 10 mm^2, cross section: 0.5 mm^2 - 10 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: blue

PTFIX 10/12X4 RD - Distribution block

3273882

https://www.phoenixcontact.com/ro/produse/3273882




Distribution block, nom. voltage: 450 V, nominal current: 32 A, number of connections: 13, connection method: Push-in connection, Load contact, cross section: 0.2 mm^2 - 6 mm^2, Push-in connection, Line contact, Rated cross section: 10 mm^2, cross section: 0.5 mm^2 - 10 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: red

PTFIX 10/12X4 GNYE - Distribution block

1153438

https://www.phoenixcontact.com/ro/produse/1153438



Distribution block, Basic terminal block with feed-in without protective conductor function, nom. voltage: 450 V, nominal current: 32 A, number of connections: 13, connection method: Push-in connection, Load contact, cross section: 0.2 mm^2 - 6 mm^2, Push-in connection, Line contact, Rated cross section: 10 mm^2, cross section: 0.5 mm^2 - 10 mm^2, mounting type: Free-hanging, color: green-yellow

PTFIX 6X4 GY - Distribution block

3273790

https://www.phoenixcontact.com/ro/produse/3273790



Distribution block, Basic terminal block, nom. voltage: 450 V, nominal current: 32 A, number of connections: 6, connection method: Push-in connection, cross section: 0.2 mm^2 - 6 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: gray

PTFIX 6X4 BU - Distribution block

3273792

https://www.phoenixcontact.com/ro/produse/3273792



Distribution block, bridged internally, nom. voltage: 450 V, nominal current: 32 A, number of connections: 6, connection method: Push-in connection, cross section: 0.2 mm^2 - 6 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: blue

PTFIX 6X4 RD - Distribution block

3273794

https://www.phoenixcontact.com/ro/produse/3273794



Distribution block, bridged internally, nom. voltage: 450 V, nominal current: 32 A, number of connections: 6, connection method: Push-in connection, cross section: 0.2 mm^2 - 6 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: red

PTFIX 6X4 GNYE - Distribution block

1154139

https://www.phoenixcontact.com/ro/produse/1154139



Distribution block, Basic terminal block with feed-in without protective conductor function, nom. voltage: 450 V, nominal current: 32 A, number of connections: 6, connection method: Push-in connection, cross section: 0.2 mm^2 - 6 mm^2, mounting type: Free-hanging, color: green-yellow

PTFIX 2X2,5 GY - Monoblock

1028067

https://www.phoenixcontact.com/ro/produse/1028067



Monoblock, Basic terminal block, nom. voltage: 450 V, nominal current: 24 A, number of connections: 2, connection method: Push-in connection, cross section: 0.14 mm^2 - 4 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: gray

PTFIX 2X2,5 BU - Monoblock

1028068

https://www.phoenixcontact.com/ro/produse/1028068



Monoblock, Basic terminal block, nom. voltage: 450 V, nominal current: 24 A, number of connections: 2, connection method: Push-in connection, cross section: 0.14 mm^2 - 4 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: blue

PTFIX 2X2,5 RD - Monoblock

1028069

https://www.phoenixcontact.com/ro/produse/1028069



Monoblock, Basic terminal block, nom. voltage: 450 V, nominal current: 24 A, number of connections: 2, connection method: Push-in connection, cross section: 0.14 mm^2 - 4 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: red

PTFIX 2X2,5 GNYE - Monoblock

1091665

https://www.phoenixcontact.com/ro/produse/1091665



Monoblock, Basic terminal block without protective conductor function, nom. voltage: 450 V, nominal current: 24 A, number of connections: 2, connection method: Push-in connection, cross section: 0.14 mm^2 - 4 mm^2, mounting type: Free-hanging, color: green/yellow

PTFIX-NS35 - DIN rail adapter

3274054

https://www.phoenixcontact.com/ro/produse/3274054

DIN rail adapter, for NS 35 and NS 15 for accommodating 2.5 mm^2, 4 mm^2, and 10 mm^2 FIX blocks in vertical direction, color: gray



PTFIX-NS35A - DIN rail adapter

3274056

https://www.phoenixcontact.com/ro/produse/3274056

DIN rail adapter, for NS 35 for accommodating 2.5 mm^2 and 4 mm^2 FIX blocks in horizontal direction, color: gray



PTFIX-F - Flange

3274060

https://www.phoenixcontact.com/ro/produse/3274060



Flange, With screw fixing, for direct mounting of the 2.5 mm^2 and 4 mm^2 FIX blocks, depth: 21.7 mm, width: 8.6 mm, height: 28.6 mm, color: gray, mounting type: Screw mounting

FBS 2-6 - Plug-in bridge

3030336

https://www.phoenixcontact.com/ro/produse/3030336




Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: red

SK 5/3,8:FORTL.ZAHLEN 1-10 - Marker for terminal blocks

0804183:0001

https://www.phoenixcontact.com/ro/produse/0804183:0001




Marker card, self-adhesive, horizontally labeled with the consecutive numbers: 1 ... 10, 10-section marker strips with 12 identical decades, white, for terminal block width: 5 mm, mounting type: adhesive

SK 5/3,8:FORTL.ZAHLEN 11-20 - Marker for terminal blocks

0804183:0011

https://www.phoenixcontact.com/ro/produse/0804183:0011




Marker card, self-adhesive, horizontally labeled with the consecutive numbers: 11 ... 20, 10-section marker strips with 12 identical decades, white, for terminal block width: 5 mm, mounting type: adhesive

SK 6,2/3,8:FORTL.ZAHLEN 1-10 - Marker for terminal blocks

0804374:0001

https://www.phoenixcontact.com/ro/produse/0804374:0001




Marker card, self-adhesive, horizontally labeled with the consecutive numbers: 1 ... 10, 10-section marker strips with 12 identical decades, white, for terminal block width: 6.2 mm, mounting type: adhesive

SK 6,2/3,8:FORTL.ZAHLEN 11-20 - Marker for terminal blocks

0804374:0011

https://www.phoenixcontact.com/ro/produse/0804374:0011



Marker card, self-adhesive, horizontally labeled with the consecutive numbers: 11 ... 20, 10-section marker strips with 12 identical decades, white, for terminal block width: 6.2 mm, mounting type: adhesive

CASE PTFIX L-BOXX REV2 DE - System package

1164787

https://www.phoenixcontact.com/ro/produse/1164787

Date tehnice

Notes

General	PTFIX in a practical Sortimo L-BOXX 102 system case. Now also for 10 mm² feed-ins. 92 distribution blocks, among other features with feed-in contact up to 10 mm² and pick-up contact up to 6 mm², 53 DIN rail adapters, 16 screw flanges, plug-in bridges, and marking material

Product properties

Product type	Distributor terminal block

Dimensions

Width	445 mm
Height	358 mm
Depth	118 mm

Material specifications

Color	black (RAL 9005)

Phoenix Contact 2025 © - Toate drepturile rezervate
https://www.phoenixcontact.com

PHOENIX CONTACT România
Splaiul Unirii 165 Timpuri Noi Square TNO1, Etaj 1
Bucuresti 030133
+40 21 350 88 12 - 3
sales.ro@phoenixcontact.com