CASE PTFIX L-BOXX DE - System package

1092040

https://www.phoenixcontact.com/ro/produse/1092040

Vă rugăm să țineți cont de faptul că datele afișate în acest document PDF au fost generate din catalogul nostru online. Datele complete sunt disponibile în documentația pentru utilizator. În cazul descărcărilor, se aplică Termenii și condițiile generale de utilizare ale companiei noastre.



PTFIX set in a practical Sortimo L-BOXX 102 system case. 90 distribution blocks, including with feed-in contact (rated cross-section 6 mm^2) and pick-off contacts (rated cross-section 2.5 mm^2), 40 monoblocks (rated cross-section 2.5 mm^2), 60 DIN rail adapters, 20 screw flanges, jumpers, and marking material

Setul este alcătuit din

PTFIX 6/12X2,5 GY - Distribution block

3273352

https://www.phoenixcontact.com/ro/produse/3273352



Distribution block, Basic terminal block with supply, nom. voltage: 450 V, nominal current: 24 A, number of connections: 13, connection method: Push-in connection, Load contact, cross section: 0.14 mm^2 - 4 mm^2, Push-in connection, Line contact, Rated cross section: 6 mm^2, cross section: 0.5 mm^2 - 10 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: gray

PTFIX 6/12X2,5 BU - Distribution block

3273354

https://www.phoenixcontact.com/ro/produse/3273354



Distribution block, Basic terminal block with supply, nom. voltage: 450 V, nominal current: 24 A, number of connections: 13, connection method: Push-in connection, Load contact, cross section: 0.14 mm^2 - 4 mm^2, Push-in connection, Line contact, Rated cross section: 6 mm^2, cross section: 0.5 mm^2 - 10 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: blue

PTFIX 6/12X2,5 RD - Distribution block

3273356

https://www.phoenixcontact.com/ro/produse/3273356



Distribution block, Basic terminal block with supply, nom. voltage: 450 V, nominal current: 24 A, number of connections: 13, connection method: Push-in connection, Load contact, cross section: 0.14 mm^2 - 4 mm^2, Push-in connection, Line contact, Rated cross section: 6 mm^2, cross section: 0.5 mm^2 - 10 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: red

PTFIX 6/12X2,5 GNYE - Distribution block

1091671

https://www.phoenixcontact.com/ro/produse/1091671



Distribution block, Basic terminal block with feed-in without protective conductor function, nom. voltage: 450 V, nominal current: 24 A, number of connections: 13, connection method: Push-in connection, Load contact, cross section: 0.14 mm^2 - 4 mm^2, Push-in connection, Line contact, Rated cross section: 6 mm^2, cross section: 0.5 mm^2 - 10 mm^2, mounting type: Free-hanging, color: green/yellow

PTFIX 6X2,5 GY - Distribution block

3273264

https://www.phoenixcontact.com/ro/produse/3273264




Distribution block, Basic terminal block, nom. voltage: 450 V, nominal current: 24 A, number of connections: 6, connection method: Push-in connection, cross section: 0.14 mm^2 - 4 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: gray

PTFIX 6X2,5 BU - Distribution block

3273266

https://www.phoenixcontact.com/ro/produse/3273266




Distribution block, Basic terminal block, nom. voltage: 450 V, nominal current: 24 A, number of connections: 6, connection method: Push-in connection, cross section: 0.14 mm^2 - 4 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: blue

PTFIX 6X2,5 RD - Distribution block

3273268

https://www.phoenixcontact.com/ro/produse/3273268



Distribution block, Basic terminal block, nom. voltage: 450 V, nominal current: 24 A, number of connections: 6, connection method: Push-in connection, cross section: 0.14 mm^2 - 4 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: red

PTFIX 6X2,5 GNYE - Distribution block

1091668

https://www.phoenixcontact.com/ro/produse/1091668



Distribution block, Basic terminal block without protective conductor function, nom. voltage: 450 V, nominal current: 24 A, number of connections: 6, connection method: Push-in connection, cross section: 0.14 mm^2 - 4 mm^2, mounting type: Free-hanging, color: green/yellow

PTFIX 2X2,5 GY - Monoblock

1028067

https://www.phoenixcontact.com/ro/produse/1028067



Monoblock, Basic terminal block, nom. voltage: 450 V, nominal current: 24 A, number of connections: 2, connection method: Push-in connection, cross section: 0.14 mm^2 - 4 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: gray

PTFIX 2X2,5 BU - Monoblock

1028068

https://www.phoenixcontact.com/ro/produse/1028068



Monoblock, Basic terminal block, nom. voltage: 450 V, nominal current: 24 A, number of connections: 2, connection method: Push-in connection, cross section: 0.14 mm^2 - 4 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: blue

PTFIX 2X2,5 RD - Monoblock

1028069

https://www.phoenixcontact.com/ro/produse/1028069



Monoblock, Basic terminal block, nom. voltage: 450 V, nominal current: 24 A, number of connections: 2, connection method: Push-in connection, cross section: 0.14 mm^2 - 4 mm^2, mounting type: for snapping onto a DIN rail adapter, Direct mounting with flange, Free-hanging, color: red

PTFIX 2X2,5 GNYE - Monoblock

1091665

https://www.phoenixcontact.com/ro/produse/1091665



Monoblock, Basic terminal block without protective conductor function, nom. voltage: 450 V, nominal current: 24 A, number of connections: 2, connection method: Push-in connection, cross section: 0.14 mm^2 - 4 mm^2, mounting type: Free-hanging, color: green/yellow

PTFIX-NS35 - DIN rail adapter

3274054

https://www.phoenixcontact.com/ro/produse/3274054

DIN rail adapter, for NS 35 and NS 15 for accommodating 2.5 mm^2, 4 mm^2, and 10 mm^2 FIX blocks in vertical direction, color: gray



PTFIX-NS35A - DIN rail adapter

3274056

https://www.phoenixcontact.com/ro/produse/3274056

DIN rail adapter, for NS 35 for accommodating 2.5 mm^2 and 4 mm^2 FIX blocks in horizontal direction, color: gray



PTFIX-F - Flange

3274060

https://www.phoenixcontact.com/ro/produse/3274060



Flange, With screw fixing, for direct mounting of the 2.5 mm^2 and 4 mm^2 FIX blocks, depth: 21.7 mm, width: 8.6 mm, height: 28.6 mm, color: gray, mounting type: Screw mounting

FBS 2-5 - Plug-in bridge

3030161

https://www.phoenixcontact.com/ro/produse/3030161




Plug-in bridge, pitch: 5.2 mm, number of positions: 2, length: 23 mm, color: red

SK 5/3,8:FORTL.ZAHLEN 1-10 - Marker for terminal blocks

0804183:0001

https://www.phoenixcontact.com/ro/produse/0804183:0001




Marker card, self-adhesive, horizontally labeled with the consecutive numbers: 1 ... 10, 10-section marker strips with 12 identical decades, white, for terminal block width: 5 mm, mounting type: adhesive

SK 5/3,8:FORTL.ZAHLEN 11-20 - Marker for terminal blocks

0804183:0011

https://www.phoenixcontact.com/ro/produse/0804183:0011




Marker card, self-adhesive, horizontally labeled with the consecutive numbers: 11 ... 20, 10-section marker strips with 12 identical decades, white, for terminal block width: 5 mm, mounting type: adhesive

SK 5/3,8: L1-N,PE - Marker card

0804206

https://www.phoenixcontact.com/ro/produse/0804206



Marker card, Sheet, white, labeled, horizontal: L1, L2, L3, N, PE, mounting type: adhesive, for terminal block width: 5 mm, Number of individual labels: 12, text field height: 3.8 mm, text field width: 5 mm

CASE PTFIX L-BOXX DE - System package

1092040

https://www.phoenixcontact.com/ro/produse/1092040

Date tehnice

Product properties

Product type	Distributor terminal block

Dimensions

Width	445 mm
Height	358 mm
Depth	118 mm

Material specifications

Color	black (RAL 9005)
Insulating material	PA

Mounting

Mounting type	NS 35/7,5
	NS 35/15

Phoenix Contact 2025 © - Toate drepturile rezervate
https://www.phoenixcontact.com

PHOENIX CONTACT România
Splaiul Unirii 165 Timpuri Noi Square TNO1, Etaj 1
Bucuresti 030133
+40 21 350 88 12 - 3
sales.ro@phoenixcontact.com