Product datasheet
FV2-5-RK



Feldverteiler - Reihenklemmen

Order number: 7110706
Type: FV2-5-RK

Große Verteiler für die intelligente Installationstechnik

- Großzügige Kabeleinführungen an der Unter-, Ober- und Rückseite je Feldbreite
- Obere und untere Kabeleinführung mit Durchstoßmembran, dadurch schnelle und einfache Handhabung ohne zusätzliches Werkzeug
- Alle Abdeckungen mit seitlichen Abschottungen
- Ab drei Feldbreiten mit Doppeltür
- Verschiedene Schlossvarianten möglich – auch DIN-Zylinderschloss

suitable for: Geräte bis Nennstrom 125A

Dimensions

Depth	165 mm
Height	800 mm
Width	550 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

Material

Box material	Sheet steel powder-coated
Cover material	PS
Door material	Sheet steel powder-coated

© f-tronic GmbH. All rights reserved
www.f-tronic.com

Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP43
Free of heavy metals	true
Halogen-free	-
Impact resistance	IK07
Installation type	SM
Insulation	Protection class II
Number of bays	2
Number of compartments	120
Number of rows	5
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design voltage	400 V
Permissible power loss according to DIN 43 873	

Certificates & standards

CE	true
Glow wire test	750 °C
REACH	false
RoHS	true
VDE	-

Accessories

Equipped with

© f-tronic GmbH. All rights reserved
www.f-tronic.com