




**Manuals and documents in further languages:**
https://eltako.com/redirect/SNT15-12VDC*15W

*Technical data page 17-8.*

# SNT15-12VDC/15W

**Switching power supply unit. Rated capacity 15 W. Standby loss 0.1 watt only.**

Modular devices for DIN 60715 TH35 rail mounting.
1 module = 18 mm wide, 58 mm deep.
At a load of more than 50% of the rated capacity and always if there are adjacent switching power supply units and if there are dimmers a ventilation clearance of 1/2 module must be maintained with the spacers DS12 on both sides.
Input voltage 230 V (-20% to +10%).
Efficiency 91%. Stabilised output voltage 12 V DC ±1%, low residual ripple. Short-circuit proof.
Overload and overtemperature protection through automatic shutdown. In the event of an overload, the output current is limited to 1.5 A, and the voltage drops accordingly. If the output voltage falls below 6 V or the temperature rises above the limit, the switching power supply shuts down and restarts automatically as soon as normal operating conditions are restored (autorecovery function).

| | | | |
|---|---|---|---|
| **SNT15-12VDC/15W** | Switching power supply unit 12V DC | **Art. No. 20000166** | **22,08 €/pc.** |
| **Optional: DS12** | Spacer | **Art. No. 20000010** | **2,23 €/pc.** |

Recommended retail prices excluding VAT.