

Manuals and documents in further languages:
https://eltako.com/redirect/DSZ180CEE-32A_MID

Technical data page 10-34.

DSZ180CEE-32A MID

MID

Portable three-phase energy meter with CEE plug 32 A and CEE coupling 32 A. Suitable for indoor and outdoor use. MID-compliant and therefore approved for use for billing purposes. Maximum current 32 A, standby loss 0.5 watt per path only. Protection class housing: IP68, protection class plug/coupling: IP44.

Housing dimensions 180 x 86 x 82 mm, connection cable 1.5 m (including plug and coupling).
Accuracy class B (1%).
This portable three-phase energy meter measures active energy by means of the current between input and output.
The internal power consumption of max. 0.5 watt active power per path is neither metered nor indicated.
The inrush current is 40 mA.
The display can only be read when the power supply is on. However, the consumption is saved to a non-volatile memory and is displayed immediately after a power failure.
The digital display has 7 digits. Two decimal places are indicated up to 99999.99 kWh.
Above 100000.0 kWh there is only one decimal place.
Power consumption is shown by a LED flashing at a rate of 100 times per kWh.

DSZ180CEE-32A MID	Mobile three-phase energy meter, with MID	**Art. No. 28032128**	**259,33 €/pc.**