Product data sheet

E118HF



HW Device box E118HF, 2x Ø 68mm, d=49mm, halogen-free

Product No.: 7350180

Type: E118HF

The basics for a proper hollow wall installation
- With break-outs for cables and pipes
- Integrated cable restraint for NYM cables
- Secure fixing of tubes

Measures	
Depth	49 mm
Milling hole diameter	2x Ø 68 mm

Material	
Socket material	PP

Environmental conditions	
Ambient temperature (minimum)	-25 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (24h)	35 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

Technical features	
Suitable for sheet thickness	5-40 mm
Max. cross section	2,5 mm²
Design voltage	400 V
Cable restraint	according to DIN 49073
Cable entry 3x1.5²	4
Cable entry 5x1.5²/3x2.5²	4
Cable entry 7x1.5²/5x2.5²	2
Pipe entry M20/M25	4
Pipe entry M20	6

© f-tronic GmbH. All rights reserved
www.f-tronic.de

Certificates & Standards	
VDE	true
CE	true
Glow wire test	850 °C
REACH	false
RoHS	true
Standards	• DIN EN 60670-1(VDE 0606-1) • DIN EN 60670-22 (VDE 0606-22)

Properties	
Installation type	HW
Degree of protection (IP)	IP30
Halogen-free	true
Free of heavy metals	true
PVC-free	true
Silicone-free	true

© f-tronic GmbH. All rights reserved
www.f-tronic.de