Product datasheet
JUMBO48K



HW/FM communications distributor JUMBO K

Order number: 7250033
Type: JUMBO48K

Innovative solutions for communications distribution

- For hollow wall and flush installation
- For installation of multimedia applications (e.g .: Telecommunications and CATV distribution)
- Convenient access to hardware components (e.g .: modem, wireless router, switch)
- Standard 3-way socket with staggered slots
- Ventilation slots in the door for heat dissipation

suitable for:

Dimensions	
Depth	98 mm
Height	775 mm
Height of HW cut-out	735 mm
Height of mounting recess	768 mm
Plaster compensation	15 mm
Width	365 mm
Width of HW cut-out	323 mm
Width of mounting recess	359 mm

Material	
Box material	PS
Cover material	PS
Door material	Sheet steel powder-coated

Environmental conditions	
Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

© f-tronic GmbH. All rights reserved
www.f-tronic.com

Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Installation type	
Insulation	Protection class II
Number of rows	4
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design current	63 A
Design voltage	400 V
Suitable for sheet thickness	10-45 mm

Certificates & standards

CE	true
Glow wire test	850 °C
REACH	true
RoHS	true
VDE	-

Accessories

Equipped with	1x door with frame (T+RJUMBO48K) 1x Patch-Panel (PATCH12) 3x mounting plate 1x 3-way socket (STECKD3) 1x hollow wall anchor set (HWA-Set) 1x connection bracket (VK-Set)
Recommended purchase	Wall claw set (MK-Set) Mounting bracket set (MH-Set)

© f-tronic GmbH. All rights reserved
www.f-tronic.com