



Manuals and documents in further languages:
https://eltako.com/redirect/KR09-12V-UC

Technical data page 12-19.
Housing for operating instructions GBA14 page 1-48 chapter 1.


KR09-12V UC

1 NO contact potential free 6 A/250 V AC. 230 V LED lamps up to 50 W, incandescent lamp load 500 W. No standby loss. Safe isolation according to DIN EN 61140 and DIN EN 60664-1; therefore, these devices can also be used as coupling relays.

Modular device for DIN-EN 60715 TH35 rail mounting. 1/2 module = 9 mm wide, 55 mm deep.
State-of-the-art hybrid technology combines advantages of nonwearing electronic control with high capacity of special relays.
Control voltages 12 V UC.
Contact position indicator with LED. Control power demand 0.2 W only.

KR09-12V UC	Coupling relay, 1 NO contact 6 A	**Art. No. 22100705**	**47,28 €/pc.**





Manuals and documents in further languages:
https://eltako.com/redirect/KR09-24V-UC

Technical data page 12-19.
Housing for operating instructions GBA14 page 1-48 chapter 1.

KR09-24V UC

1 NO contact potential free 6 A/250 V AC. 230 V LED lamps up to 50 W, incandescent lamp load 500 W. No standby loss. Safe isolation according to DIN EN 61140 and DIN EN 60664-1; therefore, these devices can also be used as coupling relays.

Modular device for DIN-EN 60715 TH35 rail mounting. 1/2 module = 9 mm wide, 55 mm deep.
State-of-the-art hybrid technology combines advantages of nonwearing electronic control with high capacity of special relays.
Control voltages 24 V UC.
Contact position indicator with LED. Control power demand 0.2 W only.

KR09-24V UC	Coupling relay, 1 NO contact 6 A	**Art. No. 22100706**	**43,57 €/pc.**





Manuals and documents in further languages:
https://eltako.com/redirect/KR09-230V

Technical data page 12-19.
Housing for operating instructions GBA14 page 1-48 chapter 1.

KR09-230V

1 NO contact potential free 6 A/250 V AC. 230 V LED lamps up to 50 W, incandescent lamp load 500 W. No standby loss. Safe isolation according to DIN EN 61140 and DIN EN 60664-1; therefore, these devices can also be used as coupling relays.

Modular device for DIN-EN 60715 TH35 rail mounting. 1/2 module = 9 mm wide, 55 mm deep.
State-of-the-art hybrid technology combines advantages of nonwearing electronic control with high capacity of special relays.
Control voltages 230 V.
Contact position indicator with LED. Control power demand 0.2 W only.

KR09-230V	Coupling relay, 1 NO contact 6 A	**Art. No. 22100730**	**43,57 €/pc.**

Recommended retail prices excluding VAT.