Product datasheet
UPV48+8ST



FM small distributor JUMBO with screw clamp

Order number: 7210031
Type: UPV48+8ST

Simple and reliable for flush mounting

suitable for:

Dimensions

Depth	98 mm
Height	775 mm
Height of mounting recess	768 mm
Plaster compensation	15 mm
Width	365 mm
Width of mounting recess	359 mm

Material

Box material	PS
Cover material	PS
Door material	

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

© f-tronic GmbH. All rights reserved
www.f-tronic.com

Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	true
Installation type	FM
Insulation	Protection class II
Number of compartments	56
Number of rows	4
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Cable entry	backside: 8x M25
Design current	63 A
Design voltage	400 V
Permissible power loss according to DIN 43 873	

Certificates & standards

CE	true
Glow wire test	650 °C
REACH	true
RoHS	true
Standards	• DIN EN 60670-1 • DIN EN 60670-24 • DIN EN 61439-1 • DIN EN 61439-3 • DIN 43871
VDE	true

Accessories

Equipped with	1x door with frame (T+RJUMBO48+8) 1x PE screw terminal (KPE34) 1x N-N screw terminal (KN17N)

© f-tronic GmbH. All rights reserved
www.f-tronic.com