# Product datasheet
HWV48+8ST



**HW small distributor JUMBO with screw clamp**

Order number: 7230018
Type: HWV48+8ST

Simple and reliable for hollow wall mounting

suitable for:

**Dimensions**

| | |
|---|---|
| Depth | 98 mm |
| Height | 775 mm |
| Height of HW cut-out | 735 mm |
| Width | 365 mm |
| Width of HW cut-out | 323 mm |

**Environmental conditions**

| | |
|---|---|
| Ambient temperature (24h) | 35 °C |
| Ambient temperature (maximum) | 40 °C |
| Ambient temperature (minimum) | -25 °C |
| Max. rel. humidity at 25°C (short term) | 95 % |
| Max. rel. humidity at 40°C | 50 % |

**Material**

| | |
|---|---|
| Box material | PS |
| Cover material | PS |
| Door material | |


© f-tronic GmbH. All rights reserved
www.f-tronic.com

### Properties

| | |
|---|---|
| Can be lead sealed | true |
| Colour | White |
| Degree of protection (IP) | IP30 |
| Free of heavy metals | true |
| Halogen-free | - |
| Impact resistance | IK07 |
| Installation type | HW |
| Insulation | Protection class II |
| Number of compartments | 56 |
| Number of rows | 4 |
| PVC-free | true |
| Silicone-free | true |
| Stackable | true |
| Weather-resistant | - |

### Technical features

| | |
|---|---|
| Design current | 63 A |
| Design voltage | 400 V |
| Permissible power loss according to DIN 43 873 | |
| Suitable for sheet thickness | 10-45 mm |

### Certificates & standards

| | |
|---|---|
| CE | true |
| Glow wire test | 850 °C |
| REACH | true |
| RoHS | true |
| Standards | • DIN EN 60670-1<br>• DIN EN 60670-24<br>• DIN EN 61439-1<br>• DIN EN 61439-3<br>• DIN 43871 |
| VDE | true |

### Accessories

| | |
|---|---|
| Equipped with | 1x door with frame (T+RJUMBO48+8)<br>1x PE screw terminal (KPE34)<br>1x N-N screw terminal (KN17N)<br>1x hollow wall anchor set (HWA-Set) |
| Recommended purchase | |


© f-tronic GmbH. All rights reserved
www.f-tronic.com