Product datasheet
HWV60+10ST



HW small distributor JUMBO with screw clamp

Order number: 7230035
Type: HWV60+10ST

Simple and reliable for hollow wall mounting

suitable for:

Dimensions	
Depth	98 mm
Height	900 mm
Height of HW cut-out	860 mm
Width	365 mm
Width of HW cut-out	323 mm

Environmental conditions	
Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

Material	
Box material	PS
Cover material	PS
Door material	

© f-tronic GmbH. All rights reserved
www.f-tronic.com

Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Impact resistance	IK07
Installation type	HW
Insulation	Protection class II
Number of compartments	70
Number of rows	5
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design current	63 A
Design voltage	400 V
Suitable for sheet thickness	10-45 mm

Certificates & standards

CE	true
Glow wire test	850 °C
REACH	true
RoHS	true
Standards	• DIN EN 60670-1 • DIN EN 60670-24 • DIN EN 61439-1 • DIN EN 61439-3 • DIN 43871
VDE	true

Accessories

Equipped with	
Recommended purchase	

© f-tronic GmbH. All rights reserved
www.f-tronic.com