Product datasheet
JUMBO36+6TS



HW/FM small distributor JUMBO with support frame

Order number: 7250109
Type: JUMBO36+6TS

Preassemblable with System
- Optionally, can be used for flush or hollow wall mounting
- Support frame for easy pre-assembly of devices and equipment

- Generous wiring space
- Strain relief possible
- Packaging can be used as plaster protection
- Suitable with HWA-Set for hollow wall installation (p.119)

Dimensions

Depth	98 mm
Height	650 mm
Width	365 mm

Material

Box material	PS
Cover material	PS
Door material	

© f-tronic GmbH. All rights reserved
www.f-tronic.com

Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP30
Impact resistance	IK07
Installation type	
Number of compartments	
Number of rows	3
Stackable	true

Technical features

Design current	63 A
Design voltage	400 V
Suitable for sheet thickness	10-45 mm

Certificates & standards

REACH	true
RoHS	true
VDE	true

Accessories

Equipped with	1x door with frame (T+RJUMBO36+6) 1x PE plug-in terminal (SKPE34) 1x N plug-in terminal (SKN34) 1x N-N plug-in terminal (SKN17N)
Recommended purchase	Hollow wall anchor set (HWA-Set) Wall claw set (MK-Set) Mounting bracket set (MH-Set) Cover strip (ADS12W)

© f-tronic GmbH. All rights reserved
www.f-tronic.com