Product datasheet
JUMBO60-3



HW/FM small distributor JUMBO Twin

Order number: 7250068
Type: JUMBO60-3

Double Power in distribution

- Generous wiring space
- For flush and hollow wall installation
- Ventilation slots in the door for heat dissipation
- Optimal combination of circuit power and communications distribution
- Variants with WiFi door available
- 5-row housing with 2 or 3 row distribution and corresponding communication field
- Two distributors combined into one spacesaving unit

Dimensions

Depth	98 mm
Height	900 mm
Height of HW cut-out	860 mm
Height of mounting recess	893 mm
Plaster compensation	15 mm
Width	365 mm
Width of HW cut-out	323 mm
Width of mounting recess	359 mm

Material

Box material	PS
Cover material	PS
Door material	Sheet steel powder-coated

© f-tronic GmbH. All rights reserved
www.f-tronic.com

Properties

Can be lead sealed	true
Colour	white, similar to RAL 9016
Impact resistance	IK07
Installation type	
Number of compartments	42
Stackable	true

Technical features

Suitable for sheet thickness	8-40 mm

Certificates & standards

REACH	true
RoHS	true / exception 6c
Standards	• DIN EN 60670-1 • DIN EN 60670-24 • DIN EN 61439-1 • DIN EN 61439-3 • DIN 43871
VDE	true

Accessories

Equipped with	1x door with frame (T+RJUMBO60K) 1x mounting plate 1x PE plug-in terminal (SKPE34) 1x N-N plug-in terminal (SKN17N) 1x socket 1x hollow wall anchor set (HWA set)
Recommended purchase	Wall claw set (MK-Set) Mounting bracket set (MH-Set) Cover strip (ADS12W)

© f-tronic GmbH. All rights reserved
www.f-tronic.com