Product datasheet
VS4-8



Distributor cabinet

Order number: 7110253
Type: VS4-8

Lots of space for maximum distribution

- Housing in an appealing design of 1mm thickness, powder coated steel plate
- Unique, push-out fastening system, thus rapid and flexible wall mounting
- Door can be removed without tools and can be affixed to the left or right
- Large door opening angle
- Includes cover strips and PE-N plug-in terminals in scope of delivery
- Retractable mounting rails
- Large wiring space behind the standard mounting rails
- Cabinet depth incl. mounting straps 210mm
- Incl. 1x ZSSKN17N and 1x ZSSKPE34 plug-in terminal per field

suitable for:

Dimensions

Depth	210 mm
Height	1250 mm
Width	1050 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

Material

Cover material	PS
Door material	Sheet steel powder-coated

© f-tronic GmbH. All rights reserved
www.f-tronic.com

Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP43
Free of heavy metals	true
Halogen-free	-
Installation type	SM
Insulation	Protection class II
Number of bays	4
Number of compartments	384
Number of rows	8
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design voltage	400 V
Permissible power loss according to DIN 43 873	

Certificates & standards

CE	true
Glow wire test	750 °C
REACH	true
RoHS	true
VDE	-

Accessories

Equipped with	N-Steckklemme 6x25mm²; 28x4mm²r PE-Steckklemme 3x25mm²;14x4mm²r 8 x Flansch mit Durchstoßmembran

© f-tronic GmbH. All rights reserved
www.f-tronic.com