# Product datasheet
VS5-6




**Distributor cabinet**

Order number: 7110244
Type: VS5-6

Lots of space for maximum distribution

- Housing in an appealing design of 1mm thickness, powder coated steel plate
- Unique, push-out fastening system, thus rapid and flexible wall mounting
- Door can be removed without tools and can be affixed to the left or right
- Large door opening angle
- Includes cover strips and PE-N plug-in terminals in scope of delivery
- Retractable mounting rails
- Large wiring space behind the standard mounting rails
- Cabinet depth incl. mounting straps 210mm
- Incl. 1x ZSSKN17N and 1x ZSSKPE34 plug-in terminal per field

suitable for:

**Dimensions**

| | |
|---|---|
| Depth | 210 mm |
| Height | 950 mm |
| Width | 1300 mm |

**Environmental conditions**

| | |
|---|---|
| Ambient temperature (24h) | 35 °C |
| Ambient temperature (maximum) | 40 °C |
| Ambient temperature (minimum) | -25 °C |
| Max. rel. humidity at 25°C (short term) | 95 % |
| Max. rel. humidity at 40°C | 50 % |

**Material**

| | |
|---|---|
| Cover material | PS |
| Door material | Sheet steel powder-coated |


© f-tronic GmbH. All rights reserved
www.f-tronic.com

### Properties

| | |
|---|---|
| Can be lead sealed | true |
| Colour | White |
| Degree of protection (IP) | IP43 |
| Free of heavy metals | true |
| Halogen-free | - |
| Installation type | SM |
| Insulation | Protection class II |
| Number of bays | 5 |
| Number of compartments | 360 |
| Number of rows | 6 |
| PVC-free | true |
| Silicone-free | true |
| Stackable | true |
| Weather-resistant | - |

### Technical features

| | |
|---|---|
| Design voltage | 400 V |
| Permissible power loss according to DIN 43 873 | |

### Certificates & standards

| | |
|---|---|
| CE | true |
| Glow wire test | 750 °C |
| REACH | true |
| RoHS | true |
| VDE | - |

### Accessories

| | |
|---|---|
| Equipped with | N-Steckklemme 6x25mm²; 28x4mm²r<br>PE-Steckklemme 3x25mm²;14x4mm²r<br>10 x Flansch mit Durchstoßmembran |


© f-tronic GmbH. All rights reserved
www.f-tronic.com