Product datasheet
UP30



FM Device socket box, solid

Order number: 7310103
Type: UP30

Versatile applications - Solid construction

- Extremely solid material, high wall thickness
- Flexible installation by variable dividers

Dimensions	
Depth	63 - 63 mm
Height	71 mm
Internal depth	62 mm
Length	71 mm
Width	213 mm

Environmental conditions	
Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

© f-tronic GmbH. All rights reserved
www.f-tronic.com

Properties

Can be lead sealed	-
Colour	Black
Degree of protection (IP)	IP20
Free of heavy metals	true
Halogen-free	true
Installation type	FM
PVC-free	true
Silicone-free	true
Stackable	-
Weather-resistant	-

Technical features

Cable entry flat cable 20x10mm	20
Design voltage	400 V
max. cross section	2,5 mm²
Pipe entry M20	14

Certificates & standards

CE	true
Glow wire test	650 °C
REACH	false
RoHS	true
VDE	-

Accessories

Equipped with	None

© f-tronic GmbH. All rights reserved
www.f-tronic.com