Product datasheet
E135



HW Device socket E135

Order number: 7350167
Type: E135

The basics for a proper hollow wall installation

- With break-outs for cables
- Integrated cable restraint for NYM cables
- Extra slim design

Dimensions

Depth	35 - 35 mm
Diameter	68 mm
Internal depth	34 mm
Milling hole diameter	Ø 68 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

Material

Socket material	PP

© f-tronic GmbH. All rights reserved
www.f-tronic.com

Properties

Can be lead sealed	false
Colour	Orange
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Installation type	HW
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Cable entry 3x1.5²	4
Design voltage	400 V
max. cross section	2,5 mm²
Suitable for sheet thickness	5-25 mm

Certificates & standards

CE	true
Glow wire test	850 °C
REACH	false
RoHS	true
VDE	REGISTERED

Accessories

Equipped with	None

© f-tronic GmbH. All rights reserved
www.f-tronic.com