Product datasheet
E118HF



HW Device socket E118HF, halogenfree

Order number: 7350162
Type: E118HF

The basics for a proper hollow wall installation

- With break-outs for cables and pipes
- Integrated cable restraint for NYM cables
- Secure fixing of tubes

Dimensions

Depth	50 - 50 mm
Diameter	68 mm
Internal depth	47 mm
Length	143 mm
Milling hole diameter	2x Ø 68 mm
Width	73 mm

Material

Socket material	PP

Environmental conditions

Ambient temperature (24h)	°C
Ambient temperature (maximum)	°C
Ambient temperature (minimum)	°C
Max. rel. humidity at 25°C (short term)	%
Max. rel. humidity at 40°C	%

© f-tronic GmbH. All rights reserved
www.f-tronic.com

Properties

Can be lead sealed	-
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	true
Installation type	HW
PVC-free	true
Silicone-free	true
Stackable	-
Weather-resistant	-

Technical features

Cable entry 3x1.5²	8
Cable entry 5x1.5²/3x2.5²	6
Design voltage	400 V
max. cross section	2,5 mm²
Pipe entry M20	6
Suitable for sheet thickness	5-40 mm

Certificates & standards

CE	true
Glow wire test	°C
REACH	false
RoHS	true
Standards	• DIN EN 60670-1(VDE 0606-1) • DIN EN 60670-22 (VDE 0606-22)
VDE	true

Accessories

Equipped with	None

© f-tronic GmbH. All rights reserved
www.f-tronic.com