Product datasheet
E815



HW Connection socket E815

Order number: 7350046
Type: E815

HW distribution socket boxes E815, diameter: 120mm, depth:65mm. incl. cover. Colour orange.

Dimensions

Depth	65 - 65 mm
Diameter	120 mm
Internal depth	64 mm
Milling hole diameter	Ø 120 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

Material

Socket material	PP

© f-tronic GmbH. All rights reserved
www.f-tronic.com

Properties

Can be lead sealed	-
Colour	Orange
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Installation type	HW
PVC-free	true
Silicone-free	true
Stackable	-
Weather-resistant	-

Technical features

Cable entry 3x1.5²	12
Cable entry 5x1.5²/3x2.5²	12
Design voltage	400 V
max. cross section	4 mm²
Pipe entry M20/M25	2/2
Suitable for sheet thickness	5-40 mm

Certificates & standards

CE	true
Glow wire test	850 °C
ÖVE	true
REACH	false
RoHS	true
Standards	
VDE	-

Accessories

Equipped with	None

© f-tronic GmbH. All rights reserved
www.f-tronic.com