# Product datasheet
E1210gn




**Damp area distribution box E1210**

Order number: 7340167
Type: E1210gn

Easy to use - Stable execution

- Easy to install
- Easy to use - no need for expensive, additional tools
- With integrated push-out membranes on all four sides
- With back side membrane introduction for cables of up to 5x 2.5mm2
- Execution with and without fixing straps

| Dimensions | |
|---|---|
| Depth | 37 mm |
| Length | 80 mm |
| Width | 80 mm |

| Environmental conditions | |
|---|---|
| Ambient temperature (24h) | 35 °C |
| Ambient temperature (maximum) | 40 °C |
| Ambient temperature (minimum) | -25 °C |
| Max. rel. humidity at 25°C (short term) | 90 % |
| Max. rel. humidity at 40°C | 50 % |

| Material | |
|---|---|
| Housing material | PP/TPE |
| Lid material | PE |


© f-tronic GmbH. All rights reserved
www.f-tronic.com

### Properties

| | |
|---|---|
| Colour | Green |
| Degree of protection (IP) | IP55 |
| Halogen-free | true |
| Installation type | SM |
| Insulation | Protection class II |
| Silicone-free | true |

### Technical features

| | |
|---|---|
| Cable entry 7x1.5²/5x2.5² | 12 |
| Design voltage | 400 V |
| Ground inserts | 2 |
| max. cross section | 2,5 mm² |

### Certificates & standards

| | |
|---|---|
| CE | true |
| Glow wire test | 650 °C |
| REACH | false |
| RoHS | true |
| Standards | • DIN EN 60670-1 (VDE 0606-1)<br>• DIN EN 60670-22 (VDE 0606-22) |
| VDE | true |

### Accessories

| | |
|---|---|
| Equipped with | None |


© f-tronic GmbH. All rights reserved
www.f-tronic.com